		GST	IN: 24DCAPP9328H1ZG				Ankur Patel Mo:9726923885		
	P					ГЕСН	MACH		
Factory Address: 61, Yamuna Industrial Park, Vanch-Dhamatvan Road, Dhamatvan-382435, Gujarat, India Web: www.umapharmatechmachinerys@gmail.com Email: umapharmatechmachinerys@gmail.com									
VESSEL & AGITATOR SPECIFICATION SHEET									
	JPM-22-250L-IHF-	-15kw-LCH	H-LCO-ph	-PLC-144R-2hp	-NFLP-SMS-35m	m	Date	11-01-22	
Customer ITEM Fermenter 250L(Inbuilt Heater In Vessel)(15kw) With 0.5 tr Chiller, 2hp Compressor, Ph Controlling & PLC Controlling									
Contact Project									
Email Vessel E)etails		F-2021-22						
Total Volume(Litter)			250						
Diameter(mm) Shell Straight Height(mm)			570 1000					(二) (二) (二)	
Shell(cylindrical)			3mm thk ss 316			I DIT			
Jacket			3mm thk SS 304			U-Frank	E		
Тор			Flat Flange End Mounting(Common For Agitator and manhole)					A	
Bottom			Dished end(10% torispherical)			COL.	B	2020/12/15 14:25	
Baffle Recommendation(Off Wall)			4 Nos @ 90 Degree						
Separate manhole Front Glass			no 100 mm						
Inner Finish			Mirror Finish			-		7 7	
Outer finish			Matt Finish				•	1-111-17	
Nozzles-Stand Pressure Guage			lard suitable Tc Ferrule 1/4 coupling			- PEREN		Drugger 1 Revent	
Safety valve			1/2 coupling			C			
Top glass			100mm -2 nos						
50 Tc Connection 35 tc connection			2 nos 3 nos				New title A		
3 inch tc connection			1 nos with Blind Connection			1			
	T 05 T-		et Connection				Faller C		
			Nos -side bottom of jacket, 1 Nos-side top of jacket) os(For Pressure guage, Safety valve, Air Valve)			10AP			
Total Height			to be confirmed						
Decian (Pritorio								
Design Criteria Viscosity 100 cP			SG 1.1			-			
	Pressure FV to 4 kg/cm2		Temp 130 deg C						
Mechanical Detail All SS Plate Will Be "JINDAL" make Only Agitator Details									
Model 250L-2hp-NFLP-worm@144rpm-35mmsms									
MOC Contact Parts SS 316						Shaft Diameter	35 mm 144		
MOC Non-CP MS/CS						Shaft Speed(RPM) Speed Controlling	Variable Frequency D	rive	
Sealing Gearbox (I	Elmech)		Single Mee Worm Gea	chanical Seal					
Motor HP	(Elmech)		2	NFLP, 4 Pole, Flan	ged, 3 Ph, 415 V, 50		-		
Impeller Type (From bottom) Impeller Blade		Ruston Turbine 6 Blade			Ruston Turbine 6 Blade	Ruston Turbine 6 Blade			
			L		Accessorie		0 2.000	L	
SS Filter	Housing set with 0.2 µ	PP Plated					r outlot		
Filter Cartridge			2 nos - for air inlet and air outlet Design, manufactur, supply of UPM make agitator assembly. Which includes impeller blades with hub, shaft, lantern assembly						
Scope of Supply Scope of Buyer			with bearing housing etc. Installation in scope of buyer(Plug and Play System)Electricity, Water, Drain Line In Buyer Scope						
	•		I		nel/ Automation I				
Temperature Sensor PT-100									
Ph Sensor			Online-Sterilizable(Indian Made)						
	Ph Controlling	linetic	Automatic ph control Using Peristaltic Pump(2 Nos)PLC Controlling Automatic PLC Controlling Based(Temperature With Timer)						
automatic Media Sterilization Batch Process Temperature			Automatic PLC Controlling Based						
Batch Process Lemperature Automatic PLC Controlling Based Other Equipment									
Oil Free Air Compressor 2 HP									
	Water Chiller		0.5 TR with 20L tank						
Commercial Terms & Conditions									
Unit Price(Non Negotiable)RS.			email us with top model number on (info@ssfermenterbioreactor.com) with Your Official email & Company Detail						
Price Basis Taxes & Duty(Tax Amount)			Ex Factory Works Extra as applicable at the time of dispatch, Presently GST = 18%						
Packing Amount Freight & Insurance			3% Extra(Wooden Box Charge Extra As Per Size) By purchaser						
Delivery									
Payment Terms			50 % advance, balance against proforma invoice						